

ECO-FLEX

ECO-FLEX IS A ONE-COMPONENT, SELF-LEVELING, SILYL-TERMINATED POLYETHER (HYBRID) ELASTOMERIC SEALANT AND ADHESIVE.

Eco-Flex fully cures to a firm flexible bond between PVC, concrete, glass, aluminum, painted surfaces, wood, plywood, marble, plus many other common substrates. This product is specifically formulated to offer all weather performance to meet today's Green Building Standards.

Features:

- No Mixing
- 40-minute tack free time
- VOC Compliant
- Flexible & Durable
- Paintable
- Mildew Resistant
- Non-Yellowing
- Non-Corrosive
- Color Stability and UV Resistant

AVAILABLE IN:	PART #
White	ECO629W
Tan	ECO629T
Grey	ECO629G



DIRECTIONS

1. Surface should be clean and dry.
2. Joints deeper than 1/2" should be filled with Poli-Void before applying Eco-Flex.
3. Cut Nozzle at angle to desired bead size.
4. Normal curing time is roughly 24 hours.

SPECIFICATIONS

Meets ASTM C 920, Type S, Grade P, Class 25, Use NT; TT-S-00-230C Type 1 Class A; CGSB 19.13 Class 1 Class 25.

STEGMEIER[®]

LLC

www.stegmeier.com

Toll-Free (800) 382-5430

Arlington, TX • Henderson, NV

DOWNLOAD THE STEGMEIER LLC APP

